(51) International Patent Classification 5 : C07C 67/08, B01J 8/22 B01D 3/18	A1	(11) International Publication Number: WO 90/08127 (43) International Publication Date: 26 July 1990 (26.07.90)

(54) Title: PROCESS AND APPARATUS

(57) Abstract

Esterification is carried out in a column reactor (14) in which there is a plurality of esterification trays (15) each having a predetermined liquid hold-up and containing a charge of a solid esterification catalyst thereon, e.g. an ion exchange resin containing -SO₃H and/or -COOH groups. A liquid phase containing the carboxylic acid component, e.g. a fatty acid mixture, flows down the column reactor from one esterification tray to the next downward one against an upflowing alcohol vapour stream, e.g. methanol vapour. Relatively dry alcohol vapour is injected (21) into the bottom of the column reactor. Water of esterification is removed from the top of the column reactor in the vapour stream (26), whilst ester product is recovered (23) from the sump of the reactor. As the liquid flows down the trays it encounters progressively drier alcohol and the esterification equilibrium reaction is driven further and further towards 100 % ester formation. A polishing reactor (304) operated under liquid phase conditions may follow the column reactor, the ester-containing product from which is mixed with further alcohol before admission to the polishing reactor.

- 1 -

PROCESS AND APPARATUS

This invention relates to a process and apparatus
for the production of carboxylic acid esters.

Esterification is a well known equilibrium limited
reaction involving reaction of a mono-, di- or
polycarboxylic acid (or, in suitable cases, an acid
anhydride) with an alcohol or phenol component. Such an
alcohol or phenol component can be mono, di- or polyhydric.

In the formation of a monoester, for example, the
reaction can be summarised:

$$R^1COOH + R^2OH \rightleftharpoons R^1COOR^2 + H_2O, \qquad (1),$$

where R^1 is a hydrogen atom or a monovalent organic radical
and R^2 is a monovalent organic radical. When an acid
anhydride is used as the acid component, the reaction occurs
in two stages:

$$R^3 \begin{array}{c} CO \\ \diagdown \\ CO \end{array} O + R^4OH \rightleftharpoons R^3 \begin{array}{c} COOH \\ \diagdown \\ COOR^4 \end{array} \qquad (2); \text{ and}$$

$$R^3 \begin{array}{c} COOH \\ \diagdown \\ COOR^4 \end{array} + R^4OH \rightleftharpoons R^3 \begin{array}{c} COOR^4 \\ \diagdown \\ COOR^4 \end{array} + H_2O \qquad (3)$$

where R^3 is a divalent organic radical and R^4 is a
monovalent organic radical.

Although the reaction of equation (2) above will
normally proceed in the absence of added catalyst and
although the organic acid may autocatalyse reactions (1) and
(3) to some extent, it is normal practice to add a catalyst
to the esterification reaction mixture in order to
accelerate the reaction.

Perhaps the most widely used catalysts are
sulphuric acid and organic sulphonic acids, such as p-
toluenesulphonic acid. Although these catalysts are
efficient, they are homogeneous catalysts and a
neutralisation step is necessary before ester purification

SUBSTITUTE SHEET

- 2 -

can be attempted. Typically washing with an alkali, such as
sodium hydroxide solution, is used in such a neutralisation
step. As esterification is an equilibrium process, a
disadvantage of this procedure is that the washing step also
results in removal of any unreacted carboxylic acid
component in the wash liquor. Normally it is uneconomic to
attempt to recover the unreacted acid from its salt in the
wash liquor so that this may represent a significant loss of
process efficiency. In addition some ester may be lost in
this washing step. The losses of ester in the aqueous
alkali phase will depend on the solubility of the ester in
such solutions. The sodium salt of a partially esterified
polycarboxylic acid will also be soluble in the aqueous
alkali liquor. Loss of such partially esterified
polycarboxylic acid will, in this case, represent a loss
both of acid moieties and also of alcohol moieties.
Furthermore the disposal of the wash liquor may present
environmental problems which may be aggravated by the
presence of the organic carboxylic acid salt in the wash
liquor. In addition, particularly when long chain fatty
acids are involved, problems may arise in the washing step
due to formation of emulsions that are stabilised by the
alkali metal fatty acid salts, which are surface active, and
that are often difficult to separate into their component
aqueous and organic phases. The stability of such emulsions
is known to vary in an erratic way, thus making the design
of the organic phase/aqueous phase separation equipment
difficult. Therefore it is difficult to practise an
esterification process with a homogeneous catalyst on a
continuous basis. As a result batch processing is usually
adopted, a factor which may affect product quality from
batch to batch. An additional disadvantage of the use of
such homogeneous catalysts is the risk of contamination of
the ester with sulphur-containing components. Such
sulphur-containing components can interfere seriously with

SUBSTITUTE SHEET

- 3 -

subsequent chemical processing steps.

Recently there has been proposed, as a result of work carried out in our laboratories, a continuous process for the production of dialkyl maleates which utilises an acidic ion exchange resin as catalyst. This proposal is described in EP-A-0255399 and in WO-A-88/00937. According to this proposal a dialkyl maleate is produced by flowing a liquid feed mixture containing monoalkyl maleate in countercurrent to a flow of vaporous alkanol vapour, so that the liquid phase encounters progressively drier alkanol vapour in passage through the catalyst-containing esterification zone or zones. In one embodiment the resin catalyst is wrapped in mesh packages and packed as a trickle bed in a tower down which the liquid phase flows against an upcoming alcohol vapour. In another embodiment a plurality of continuously stirred tank reactors is used with the liquid phase passing from one reactor to the next succeeding reactor of the series whilst the alcohol vapour flows from each reactor to the preceding reactor of the series.

The proposals described in EP-A-0255399 and in WO-A-88/00937 are somewhat complex. The tower concept requires that the ion exchange resin be wrapped in individual mesh packages. The multi-reactor system requires continuous operation of stirrer motors and is somewhat difficult in practice to control, besides requiring a significant site area for erection.

A form of gas-liquid contact column is described in US-A-3394927. DE-B-1009749 describes a column reactor for hydrogenating unsaturated oils. In FR-A-1384683 there is described a multi-compartment column reactor in which catalytic reactions can be carried out between a gas and a liquid flowing in countercurrent from compartment to compartment and in co-current within each compartment.

The present invention seeks to produce an improved continuous process for production of esters using ion

- 4 -

exchange resin catalysts which is simple in operation and
obviates the need to provide continuous mechanical stirring,
whilst permitting use of free particulate ion exchange
resin.

According to the present invention there is
provided a continuous process for the production of
carboxylic acid esters by reaction of a carboxylic acid
component selected from mono-, di- and polycarboxylic acids,
anhydrides thereof, and mixtures thereof, and of an alcohol
component selected from mono-, di- and polyhydric alcohols,
phenols and mixtures thereof, in which the carboxylic acid
component and alcohol component are passed in countercurrent
through an esterification zone maintained under
esterification conditions and containing a solid
esterification catalyst selected from particulate ion
exchange resins having sulphonic acid groups, carboxylic
acid groups or both, characterised in that the
esterification zone comprises a column reactor provided with
a plurality of esterification trays mounted one above
another, each adapted to hold a predetermined liquid volume
and a charge of solid esterification catalyst thereon,
liquid downcomer means associated with each esterification
tray adapted to allow liquid phase to pass down the column
reactor from that esterification tray but to retain solid
esterification catalyst thereon, and vapour upcomer means
associated with each esterification tray adapted to allow
vapour to enter that esterification tray from below and to
agitate the mixture of liquid and solid esterification
catalyst on that tray, that the less volatile component of
the carboxylic acid component and of the alcohol component
is supplied in liquid phase to the uppermost one of said
plurality of esterification trays whilst the more volatile
component of the carboxylic component and of the alcohol
component is supplied in vapour form beneath the lowermost
one of said plurality of esterification trays, that vapour

- 5 -

comprising said more volatile component and water of
esterification is recovered from an upper part of the column
reactor, and that said carboxylic acid ester is recovered
from a lower part of the column reactor.

The invention further provides apparatus for use in
the production of a carboxylic acid ester by reaction of a
carboxylic acid component selected from mono-, di- and
polycarboxylic acids, anhydrides thereof, and mixtures
thereof, and of an alcohol component selected from mono-,
di- and polyhydric alcohols, phenols and mixtures thereof,
comprising a column reactor provided with a plurality of
esterification trays mounted one above another, each adapted
to hold a predetermined liquid volume and a charge of a
solid esterification catalyst thereon, liquid downcomer
means associated with each esterification tray adapted to
allow liquid phase to pass down the column reactor from that
esterification tray but to retain solid esterification
catalyst thereon, vapour upcomer means associated with each
esterification tray adapted to allow vapour to enter that
esterification tray from below and to agitate the mixture of
liquid and solid esterification catalyst on that
esterification tray, means for supplying the less volatile
component of the carboxylic acid component and of the
alcohol component in liquid phase to an upper part of the
column reactor above the uppermost esterification tray,
means for supplying the more volatile component of the
carboxylic acid component and of the alcohol component in
vapour form to a lower part of the column reactor below the
lowermost esterification tray, means for recovering
carboxylic acid ester from a lower part of the column
reactor below the lowermost esterification tray, and means
for recovering from an upper part of the column reactor
above the uppermost esterification tray a vaporous stream
comprising said more volatile component and water of
esterification.

- 6 -

The process of the invention utilises the vaporous stream of the more volatile of the two components, i.e. the more volatile out of the carboxylic acid component and the alcohol component, to carry away water of esterification produced in the esterification reactor but without carrying with it significant quantities of the other, i.e. the less volatile one, of the two components or of the carboxylic acid ester. For this reason it is essential that the boiling point of the vaporous mixture exiting the esterification reactor, or of the highest boiling compound present in that vaporous mixture, shall be significantly lower, at the pressure prevailing in the uppermost stage of the esterification reactor, than the boiling point at that pressure either of the less volatile one of the two components, i.e. the less volatile out of the carboxylic acid component and the alcohol component, or of the carboxylic acid ester product. By the term "significantly lower" we mean that the boiling point difference shall be at least about 20°C, and preferably at least about 25°C, at the relevant operating pressure.

As examples of monoesterification reactions that can be conducted according to the present invention there can be mentioned the production of alkyl esters of aliphatic monocarboxylic acids from alkanols and aliphatic monocarboxylic acids or anhydrides thereof. Such monocarboxylic acids may contain, for example, from about 6 to about 26 carbon atoms and may include mixtures of two or more thereof. Alkyl esters derived from alkanols containing 1 to about 10 carbon atoms are of especial importance.

Such monocarboxylic acids include fatty acids such as decanoic acid, dodecanoic acid, tetradecanoic acid, hexadecanoic acid, octadecanoic acid, octadecenoic acid, linoleic acid, eicosanoic acid, isostearic acid and the like, as well as mixtures of two or more thereof. Mixtures of fatty acids are produced commercially by hydrolysis of

naturally occurring triglycerides of vegetable origin, such
as coconut oil, rape seed oil, and palm oils, and
triglycerides of animal origin, such as lard, tallow and
fish oils. If desired, such mixtures of acids can be
subjected to distillation to remove lower boiling acids
having a lower boiling point than a chosen temperature (e.g.
C_8 to C_{10} acids) and thus produce a "topped" mixture of
acids, or to remove higher boiling acids having a boiling
point higher than a second chosen temperature (e.g. C_{22+}
acids) and thus produce a "tailed" mixture of acids, or to
remove both lower and higher boiling acids and thus produce
a "topped and tailed" mixture of acids. Such fatty acid
mixtures may also contain ethylenically unsaturated acids
such as oleic acid. These fatty acid mixtures can be
esterified with methanol to yield methyl fatty acid ester
mixtures that can be hydrogenated to yield mixtures of
alkanols, e.g. C_8 to C_{20} alkanols (often called detergent
alcohols), that are acceptable for production of detergents
without prior separation of the alkanols one from another.
Such hydrogenation can be conducted either in the liquid
phase or in the vapour phase (in which case hydrogenation
conditions are advantageously selected such that the
vaporous mixture in contact with the catalyst is always
above its dew point, preferably at least about $5^{\circ}C$ above its
dew point). As examples of suitable hydrogenation catalysts
there can be mentioned copper chromite and reduced copper
oxide-zinc oxide hydrogenation catalysts of the type
disclosed in GB-B-2116552.

Another class of carboxylic acid esters that can be
produced by the process of the invention are dialkyl esters
of aliphatic and cycloaliphatic C_4 to C_{18} saturated and
unsaturated dicarboxylic acids. These can be produced by
reaction of alkanols with the dicarboxylic acids or
anhydrides thereof, or with mixtures of the dicarboxylic
acid and its anhydride. Dialkyl oxalates, dialkyl maleates,

- 8 -

dialkyl succinates, dialkyl fumarates, dialkyl glutarates, dialkyl pimelates, and dialkyl azelaates are examples of such dicarboxylic acid esters. Other examples of such esters include dialkyl esters of tetrahydrophthalic acid. The C_1 to C_{10} alkyl esters of such dicarboxylic acids are of particular interest. Either the free dicarboxylic acid or its anhydride (if such exists) or a mixture of dicarboxylic acids and anhydride can be used as the carboxylic acid component starting material for production of such dialkyl esters. Alkyl esters of aromatic C_7 to C_{20} monocarboxylic acids and mixtures thereof can be made by a process of the invention. Benzoic acid and 1-naphthoic acid are examples of such acids.

Alkyl esters of aromatic C_8 to C_{20} dicarboxylic acids can also be produced by the process of the invention from the acids, their anhydrides and mixtures thereof.

It is also possible to produce polyalkyl esters of polycarboxylic acids by the process of the invention. Such polycarboxylic acid moieties include, for example, citric acid, pyromellitic dianhydride, and the like.

Carboxylic acid esters of dihydric and polyhydric alcohols can be produced by the process of the invention. Examples of such esters include ethylene glycol diformate, ethylene glycol diacetate, propylene glycol diformate, propylene glycol diacetate, glyceryl triacetate, hexose acetates, and the acetate, propionate and n-butyrate esters of sorbitol, mannitol and xylitol, and the like.

In the practice of the invention the more volatile component of the two, i.e. the more volatile out of the carboxylic acid component and the alcohol component, will often be the alcohol component. For example methanol will be the more volatile component in the production from fatty acid mixtures obtained by the hydrolysis of triglycerides of methyl fatty acid ester mixtures for subsequent processing, for example for production of detergent alcohols by ester

SUBSTITUTE SHEET

- 9 -

hydrogenation. On the other hand, in the production of the di-n-butyryl ester of ethylene glycol from n-butyric acid and ethylene glycol, for example, n-butyric acid will be the more volatile component. Similarly, in the production of propylene glycol diformate from propylene glycol and formic acid, the more volatile component will be the carboxylic acid component, i.e. formic acid.

The esterification conditions used in the column reactor will normally include use of elevated temperatures up to about 160°C, for example a temperature in the range of from about 80°C to about 140°C, preferably in the range of from about 100°C to about 125°C. Such operating temperatures will be determined by such factors as the thermal stability of the esterification catalyst, the kinetics of the esterification reaction and the vapour temperature of the vaporous component fed to the base of the column reactor at the relevant inlet pressure. Typical operating pressures at the vapour inlet of the column reactor range from about 0.1 bar to about 25 bar. A liquid hourly space velocity through the column reactor in the range of from about 0.1 hr^{-1} to about 10 hr^{-1}, typically from about 0.2 hr^{-1} to about 2 hr^{-1}, may be used.

The alcohol component or the carboxylic acid component or a mixture thereof may be supplied to an upper part of the column reactor in liquid form, in solution in recycled ester product or in solution in an inert solvent or diluent therefor. In some cases it may be desired to prereact the alcohol component and the carboxylic acid component prior to introduction to the column reactor. Such prereaction may be used, for example, in a case in which reaction between the two components can be initiated in the absence of added catalyst. The reaction of an acid anhydride, such as maleic anhydride or phthalic anhydride, with an alcohol component, such as an alkanol (e.g. methanol, ethanol or n-butanol) is an example of such a

SUBSTITUTE SHEET

reaction, the formation of the corresponding monoester
occurring under moderate conditions, e.g. $60^{\circ}C$ and 5 bar,
without the need of any added catalyst, according to the
following equation:

$$\begin{array}{ccc} HC - CO \\ \| \diagdown O & + R^5OH \rightleftharpoons & \begin{array}{c} HC - CO - OR^5 \\ \| \\ HC - CO - OH \end{array} \\ HC - CO \diagup \end{array} \qquad (4)$$

where R^5 is an alkyl radical, such as methyl, ethyl or n-
butyl. This monoester is still a monocarboxylic acid. In
addition some formation of diester will occur:

$$\begin{array}{c} HC - CO - OR^5 \\ \| \\ HC - CO - OH \end{array} + R^5OH \rightleftharpoons \begin{array}{c} HC - CO - OR^5 \\ \| \\ HC - CO - OR^5 \end{array} + H_2O \qquad (5).$$

The resulting reaction mixture may contain a mixture of
monoester, diester, water, and alkanol. Further alkanol can
be added, if desired, to the mixture prior to introduction
to the column reactor for conversion of the monoester to the
diester.

In other cases, even when a monocarboxylic acid
ester is the desired product, the alcohol component and the
carboxylic acid component can be reacted to equilibrium in
the presence of an acidic ion exchange resin containing
$-SO_3H$ and/or $-COOH$ groups prior to introduction of the
resulting equilibrium mixture to the column reactor.

In the process of the invention a vaporous mixture
exits the column reactor as an overhead product. Provision
may be made for scrubbing such vaporous mixture with the
more volatile component (usually the alcohol component) in
liquid form in order to wash traces of carboxylic acid ester
product and of the other component (usually the carboxylic
acid component) back into the column reactor. This overhead
product from the column reactor can be condensed and treated
in known manner to separate its constituents, the recovered
water of esterification being rejected and the more volatile
component (usually the alcohol component) being recycled for

- 11 -

re-use in as dry a form as is practicable within the
relevant economic constraints. The lower the water content
of the vapour that is supplied to the lowermost one of said
esterification trays, the further towards 100% conversion to
ester the esterification equilibrium reaction can be driven
and the lower the residual acidity of the ester containing
product recovered from the bottom of the column reactor will
be. However, a balance may often have to be struck between
the cost of providing, for example, a substantially dry
alkanol for vaporisation into the column reactor, on the one
hand, and the cost of providing and operating any additional
downstream processing facilities that may be required to
upgrade the ester product to the required quality if a less
dry alkanol is used. This will vary from alkanol to alkanol
and will depend upon the interaction between water and
alkanol (e.g. azeotrope formation) and its effect upon
alkanol/water separation. Preferably, when using an
upflowing alkanol vapour in the column reactor, the water
content of the alkanol vapour supplied to the reactor is
less than about 5 mole %, and even more preferably is less
than about 1 mole %.

The column reactor has a plurality of
esterification trays. Although two or three trays may
suffice in some cases, it will typically be necessary to
provide at least about 5 up to about 20 or more
esterification trays in the column reactor. Typically each
esterification tray is designed to provide a residence time
for liquid on each tray of from about 1 minute up to about
120 minutes, preferably from about 5 minutes to about 60
minutes.

The solid esterification catalyst may be a granular
ion exchange resin containing $-SO_3H$ and/or $-COOH$ groups.
Macroreticular resins of this type are preferred. Examples
of suitable resins are those sold under the trade marks
"Amberlyst", "Dowex", "Dow" and "Purolite" such as Amberlyst

- 12 -

13, Amberlyst 66, Dow C351 and Purolite C150.

Different solid esterification catalysts may be used on different trays of the column reactor. Moreover different concentrations of solid esterification catalyst can be used on different trays.

The charge of solid particulate or granular esterification catalyst on each tray is typically sufficient to provide a catalyst:liquid ratio on that tray corresponding to a resin concentration of at least 0.2% w/v, for example a resin concentration in the range of from about 2% w/v to about 20% w/v, preferably 5% w/v to 10% w/v, calculated as dry resin. Sufficient catalyst should be used to enable equilibrium or near equilibrium conditions to be established on the tray within the selected residence time at the relevant operating conditions. On the other hand not so much catalyst should be used on each tray that it becomes difficult to maintain the catalyst in suspension in the liquid on the tray by the agitation produced by the upflowing vapour entering the tray from below. For a typical resin catalyst a resin concentration in the range of from about 2% v/v to about 20% v/v, preferably 5% v/v to 10% v/v may be used.

The particle size of the catalyst should be large enough to facilitate retention of the catalyst on each tray by means of a screen or similar device. However, as the larger the catalyst particle size is the more difficult it is to maintain in suspension and the lower the geometrical surface area per gram, it is expedient to use not too large a catalyst particle size. A suitable catalyst particle size is in the range of from about 0.1 mm to about 5 mm.

One or more wash trays may be provided above the esterification trays in order to prevent loss of product, solvent and/or reagents from the column reactor.

In the column reactor the vapour upcomer means associated with each esterification tray may comprise a

SUBSTITUTE SHEET

sparger positioned so that, in operation, it will lie below
the surface of the mixture of liquid and solid
esterification catalyst on that tray and so that vapour
bubbles emerging therefrom will agitate said mixture of
liquid and solid particulate catalyst. The sparger may be a
ring sparger. At least one baffle means may be mounted in
the vicinity of the sparger to enhance the mixing action
thereof. For small scale operation a sparger on the axis of
the column reactor under a cylindrical baffle can be used.

In one embodiment the sparger is a ring sparger and
inner and outer annular baffle means are positioned in the
vicinity of the sparger and define an upflow zone in the
region of upflowing vapour bubbles and adjacent downflow
zones within and outside the upflow zone.

It is important to avoid stagnant zones where solid
esterification catalyst can settle out because this can lead
to excessive formation of by-products or to occurrence of
hot spots. Although mechanical stirrers can be provided on
each tray to maintain the catalyst particles suspended in
liquid, this adds somewhat to the complexity of the reactor.
It is possible, however, by suitable design of the sparger
and tray to ensure that the upflowing vapour provides
sufficient agitation in passage through the liquid on the
tray to maintain the catalyst particles in suspension. To
achieve this end it is convenient if at least a part of the
floor of one or more (and preferably all) of the
esterification trays slopes towards a zone where there is
turbulence caused by the upflowing vapour such as is to be
found under the sparger. The angle of slope is preferably
selected so as to be equal to or greater than the angle of
repose of the solid particulate esterification catalyst
under the liquid in the esterification tray. The adoption
of such a slope will tend to ensure that all of the catalyst
is in dynamic contact with the liquid during operation and
that no stagnant zones of catalyst are formed. Such

- 14 -

stagnant zones are undesirable because they can enable
undesirable side reactions or even thermal runaways to occur
in certain instances.

In a preferred apparatus the vapour upcomer means
of one or more (and preferably all) of the esterification
trays is or are provided with a liquid suckback preventer
means.

A screen means may be provided on at least one
esterification tray to hinder loss of solid esterification
catalyst from that esterification tray via its associated
downcomer means. In this way downward flow of the solid
catalyst from one esterification tray to the next lower one
can be substantially prevented.

Means may be provided for withdrawing resin from,
or adding resin to, one or more of the trays during
operation of the column reactor. For example, a conduit
having a down turned open end can extend into the interior
of a respective tray with its open lower end positioned at a
low point within the tray. By this means a slurry of
catalyst and liquid can be withdrawn in controlled manner
from the tray intermittently or continuously, as desired, or
further catalyst can be introduced in slurry form to the
trays, as desired. Catalyst withdrawn from a given tray can
be re-introduced into the column reactor, either into the
same tray or to a lower or higher one, possibly after being
given a regeneration treatment.

In order that the invention may be clearly
understood and readily carried into effect three preferred
forms of plant for continuous production of esters, and
corresponding preferred processes for use in connection
therewith, will now be described, by way of example only,
with reference to the accompanying drawings, in which:-

Figure 1 is a flow diagram of a plant for the
production of methyl esters of fatty acids constructed in
accordance with the teachings of the invention;

SUBSTITUTE SHEET

- 15 -

Figure 2 is a flow diagram of a plant for the production of a carboxylic acid ester which has a significantly higher boiling point than the alcohol from which the alcohol moiety is derived, than water, or than any alcohol/water azeotrope formed;

Figures 3 to 5 show details of parts of two designs of esterification reactor; and

Figure 6 is a flow diagram of another plant.

It will be understood by those skilled in the art that the drawings are diagrammatic and that further items of equipment such as reflux drums, pumps, vacuum pumps, temperature sensors, pressure sensors, pressure relief valves, control valves, flow controllers, level controllers, holding tanks, storage tanks, and the like may be required in a commercial plant. The provision of such ancillary items of equipment forms no part of the present invention and is in accordance with conventional chemical engineering practice.

Referring to Figure 1 of the drawings, methanol is supplied to the plant in line 1 and is admixed with recycled methanol in line 2 to form a methanol feed to the plant in line 3. A fatty acid mixture, for example a mixture of fatty acids obtained by hydrolysis of a naturally occurring triglyceride, e.g. coconut oil, followed by "topping and tailing", is fed in line 4 and mixed with the methanol feed from line 3 before flowing to a heat exchanger 5, in which its temperature is raised to 110°C. The heated acid/methanol mixture flows on in line 6 into primary esterification reactor 7, which contains a charge 8 of an ion exchange resin containing sulphonic acid and/or carboxylic acid groups, such as Amberlyst 13. (The word "Amberlyst" is a trade mark). The pressure in reactor 7 is 5 bar.

In reactor 7 part of the acid mixture is esterified by reaction with methanol to yield a corresponding mixture

SUBSTITUTE SHEET

- 16 -

of methyl fatty acid esters. There exits from reactor 7 in
line 9 a mixture of methyl esters, unreacted fatty acid,
water produced by esterification and unreacted methanol.
This mixture passes through a pressure let down valve 10
into a vapour/liquid separator 11. A vapour phase
comprising methanol and water is fed at 1.3 bar by way of
lines 12 and 13 to an upper part of an esterification
reactor 14. Reactor 14 is provided with a number of
esterification trays 15; two possible forms of
esterification tray 15 are illustrated in Figures 3 and 4
and will be described in greater detail below. In the plant
of Figure 1 there are six trays 15; however, a greater or
lesser number of such trays (e.g. any number from 3 to 5 or
7 to 20) may be provided, depending upon the nature of the
fatty acid and the reaction conditions selected.

The liquid phase from vapour/liquid separator 11 is
fed by way of line 16, pump 17 and line 18 to heat exchanger
19, in which it is heated by steam to a temperature of up to
150°C, e.g. 120°C, and then by means of line 20 to reactor
14 at a point below the entry point of line 13.

In reactor 14 the downflowing unreacted fatty acids
in the mixture in line 20 pass downwardly from each
esterification tray 15 to the next lower tray 15 against an
upflowing current of vapour comprising methanol and water of
esterification, i.e. water produced as a result of the
esterification reaction. Dry methanol vapour is supplied to
reactor 14 in line 21. Each esterification tray 15 holds a
charge of an acidic ion exchange resin, such as a resin
containing sulphonic acid groups. Amberlyst 13 is a
suitable resin. (Amberlyst is a trade mark). In passage
down column 14 any unreacted free acid encounters
progressively drier methanol vapour on each tray 15. By
designing each tray 15 to provide an appropriate liquid hold
up, it is possible to regulate the residence time on each
tray 15. By selecting a suitable number of trays 15 it is

further possible to design reactor 14 so that essentially no
free fatty acid remains in the liquid passing downwards from
the bottom tray 15 into the sump 22 of reactor 14. Methyl
ester product (i.e. a mixture of methanol and methyl esters
derived from the mixed fatty acids supplied in line 4) is
removed from sump 22 in line 23 and pumped onward by pump 24
via line 25 for further treatment or to a product refining
facility or to storage.

A mixture of methanol vapour and the water released
in the esterification reaction is recovered overhead from
reactor 14 in line 26. Liquid methanol is supplied in line
27 to an upper part of reactor 14 above the point of
connection of line 13 to provide liquid methanol on wash
tray 28.

The vapour in line 26 is fed to a methanol/water
separation column 29 which is operated at 1.3 bar and at a
head temperature of 70°C. Dry methanol vapour is recovered
overhead in line 30 and is condensed in condenser 31. The
resulting condensate is collected in drum 32 which is vented
as indicated at 33. Dimethyl ether produced as byproduct is
vented in line 33. Methanol which would otherwise be lost
along with the dimethyl ether can be recovered by providing
a chilled condenser (not shown) in line 31. Part of the
condensed methanol is recycled to column 29 from drum 32 as
a reflux stream in line 34 by means of pump 35 and lines 36
and 37. The remainder is pumped back for re-use in line 38.

The sump product from column 29 consists
essentially of water. This is withdrawn in line 39. Part
is recycled to column 29 by way of line 40, steam heated
reboiler 41 and line 42; the remainder is passed on in line
43 for effluent treatment.

Some of the dry methanol in line 38 is passed
through vaporiser 44 to provide the stream of dry methanol
vapour in line 21. The rest flows on in line 45 to provide
the recycle streams in lines 2 and 27.

- 18 -

In a modification of the plant of Figure 1 reactor
7 and vapour/liquid separator 11 are omitted and the mixture
of fatty acids and methanol is fed by way of line 46 to line
13.

In a further modification of the plant of Figure 1
lines 1 to 3 and items 6 to 12 and 16 to 20 are omitted.
Thus liquid fatty acid or fatty acid mixture is the sole
liquid feed to reactor 14 and is supplied by way of lines 4,
46 and 13. Make up methanol for the plant can be supplied
through line 47 to reflux drum 32.

Figure 2 illustrates an alternative form of plant
suitable for production of mono-, di- and polycarboxylic
acid esters which have a significantly higher boiling point
than that of the alcohol used and of any water/alcohol
azeotrope that may be formed.

In the plant of Figure 2 the same reference
numerals are used to indicate like parts to those present in
the plant of Figure 1, except that line 1 is used for
supply, not of methanol, but of a higher alcohol such as
ethanol or a higher alkanol containing up to 10 carbon
atoms. The product in line 25 is thus an ethyl or higher
ester of a mono-, di- or polycarboxylic acid. Reference
numeral 48 indicates any suitable alkanol/water separation
plant.

Similar modifications to the plant of Figure 2 can
be made to those described above, i.e. omission of items 1
to 3, 6 to 12 and 16 to 20 to permit supply of liquid fatty
acid or fatty acid mixture as the sole liquid feed to
reactor 14.

Figure 3 illustrates one form of construction of a
tray 15 of reactor 14 of the plants of Figures 1 and 2. A
horizontal diaphragm or partition 50 extends within wall 51
of reactor 14 and closes off the cross section of reactor 14
completely except for a downcomer 52 for liquid and a vapour
upcomer 53. Partition 50 has an axial frusto-conical part

SUBSTITUTE SHEET

- 19 -

54 surrounding vapour upcomer 53 and an annular sloping
portion 55 adjacent wall 51. Tray 15 can thus retain a
volume of liquid whose surface is indicated at 56 and whose
volume is determined by the height of the overflow level of
downcomer 52 above the partition 50. Each tray 15 also
supports a charge of an acidic ion exchange resin containing
$-SO_3H$ groups, such as Amberlyst 13, whose particles are
indicated diagrammatically at 57. Such ion exchange
particles are kept in suspension in the liquid on tray 15 as
a result of agitation caused by the upcoming vapour as will
be described below. To prevent escape of ion exchange
particles 57 with the liquid overflowing down downcomer 52
the top of downcomer 52 is provided with a screen 58. The
slope of frusto-conical part 54 and of sloping portion 55 is
equal to or greater than the angle of repose of the
Amberlyst 13 or other solid particulate esterification
catalyst under the liquid on esterification tray 15.

        Vapour upcomer 53 conducts upcoming vapour to a
circular sparger 59, which surrounds frusto-conical part 54,
by way of spider tubes 60. Suckback of liquid down upcomer
53 is prevented by means of an anti-suckback valve 61.

        Annular draught shrouds or baffles 62 and 63 are
positioned within the body of liquid on tray 15, one inside
and one outside circular sparger 59 to promote agitation of
the liquid/resin suspension by the upcoming vapour. The
vertical extent of shrouds 62 and 63 is not critical but
should generally be between one third and three quarters of
the vertical height between diaphragm 50 and liquid surface
56. It is preferred that shrouds 62 and 63 should be placed
in a symmetrical or near symmetrical vertical position. In
the annular zone between shrouds 62 and 63 the liquid flow
is generally upward whilst inside shroud 62 and outside
shroud 63 the general direction of liquid flow is downward.
Preferably the area of the annular zone between shrouds 62
and 63 approximately equals the sum of the areas inside

- 20 -

shroud 62 and outside shroud 63.

Reference numeral 64 indicates a downcomer from the
next tray above the one illustrated in Figure 3. The liquid
level in downcomer 64 is indicated at 65, the height H of
this liquid level above liquid level 56 on tray 15 being
fixed by the liquid level on the tray which feeds downcomer
64 (i.e. the tray above the illustrated tray 15) plus the
pressure drop through the sparger 59 on that tray (i.e. the
one above the illustrated tray 15) and the frictional
pressure drop.

In operation of reactor 14 a mono, di- or
polycarboxylic acid or mixture of acids is typically passed
downwards in liquid form in countercurrent to an upflowing
vaporous stream of alcohol. Each tray 15 acts as an
esterification zone containing a respective charge of
esterification catalyst which catalyses the esterification
reaction and the release of water of esterification. Under
the countercurrent conditions prevailing in the reactor 14
such water of esterification is vaporised and carried
upwards through reactor 14 with the upflowing alcohol
vapour. The liquid passes downwards from one tray 15 to the
next downward tray 15 and the free acid concentration in the
liquid on each tray 15 is lower than the corresponding acid
concentration in the liquid on the next higher tray 15. In
addition the liquid encounters drier and drier alcohol
vapour on each tray 15 as it passes down through reactor 14.
In this way the equilibrium of the esterification reaction
is pushed further towards ester formation, the reverse
hydrolysis reaction being effectively suppressed because the
water concentration in the liquid on the trays 15 decreases
from tray to tray in the downward direction.

By selecting a suitable number of trays 15 in
column 14 and designing each tray 15 to provide a sufficient
liquid hold up to provide the requisite residence time on
each tray it is possible to design reactor 14 so that the

- 21 -

product in line 25 contains less than about 1 mole % of carboxylic acid, together with fatty acid esters and alcohol as its principal components. By providing an adequate upflow rate for alcohol vapour the agitation caused by the vapour bubbles 66 emerging from circular sparger 59, coupled with the liquid circulation induced by the presence of draught shrouds 62 and 63, can suffice to maintain the acidic ion exchange resin particles sufficiently in suspension for esterification to proceed successfully. The surfaces of sections 54 and 55 slope towards the zone under the sparger 59 and ensure that there are no stagnant zones where significant quantities of resin can settle out of suspension. (It will be appreciated that, although Figure 3 only shows resin particles 57 in suspension in the zone between draught shrouds 62 and 63, they would in practice be present in suspension in the liquid phase outside this zone). If necessary, the volume of the upflowing vapour can be boosted by inert gas or by other vaporisable inert material, conveniently an inert material that is a byproduct of the process. For example, it is often found that an ether is found amongst the byproducts, as acidic catalysts can promote formation of an ether from the alcohol used. Thus dimethyl ether is a potential byproduct if methanol is used as the alcohol, whilst diethyl ether can be formed in reactor 14 if ethanol is the alcohol used; either material can be used, if necessary, to boost vapour upflow to provide additional agitation on trays 15 or to provide additional vapour to carry away water of esterification.

In Figure 4 there is illustrated an alternative design of esterification tray 15 suitable for use in a relatively small scale reactor 14. In this case a frusto-conical partition or diaphragm 70 extends within wall 71 of reactor 14 and closes off the cross section of reactor 14 completely except for a downcomer 72 for liquid and a vapour upcomer 73. The slope of frusto-conical diaphragm 70 is

- 22 -

equal to or greater than the angle of repose of the solid
particulate catalyst under the liquid present on tray 15.
The vapour upcomer 73 includes an axial sparger 74 provided
with a bubble cap 75 and is fitted with an anti-suckback
valve 76. Optionally bubble cap 75 can be surrounded by a
mesh screen (not shown) to prevent ingress of catalyst
particles interfering with the operation of valve 76. A
cylindrical baffle 77 surrounds sparger 74 symmetrically and
is positioned beneath the liquid level 78, the height of
which is determined by the height of the upper end of
downcomer 72. A screen 79 is fitted to the top of downcomer
72 to retain solid esterification catalyst, e.g. Amberlyst
13, on tray 15. Reference numeral 80 indicates the
downcomer from the next higher esterification tray 15 (not
illustrated). In a similar manner to that described in
relation to Figure 3 the bubbles 81 of vapour agitate the
liquid on tray 15 and maintain particles 82 of catalyst in
suspension. Baffle 77 defines an upflow zone within baffle
77 and a downflow zone outside baffle 77. Preferably the
areas of the two zones are substantially equal. This design
ensures that, so far as is possible, no stagnant zones where
catalyst particles can sediment are formed.

If desired the feed line 20 or 13 in the plants of
Figures 1 and 2 can be arranged to discharge onto a tray,
similar to tray 15 of Figure 3 or Figure 4, which does not
hold a charge of ion exchange resin. One or more alkanol
wash trays may be provided above the connection of feed line
20 or 13 so that the vapours are scrubbed with a minor
amount of liquid alkanol before exiting reactor 14 in line
26 so as to limit the amount of acid or ester to traces
therein.

Figure 5 illustrates a further design of
esterification tray 15 suitable for use in a laboratory
scale reactor 14 or in a commercial scale reactor 14. This
comprises a generally frusto-conical partition or diaphragm

SUBSTITUTE SHEET

- 23 -

250 which extends within wall 251 of reactor 14. The slope
of the upper surface of diaphragm 250 is greater than the
angle of repose of the solid particulate catalyst. A vapour
upcomer 252 is fitted with a cap 253 with a dependent skirt
of mesh 254. Downcomer 255 is fitted with a mesh cap 256
and with a seal bucket 257. The upper end of downcomer 255
is positioned so as to provide a suitable retention volume
for liquid on tray 15 whilst mesh skirt 254 and mesh cap 256
retain the charge of resin particles on diaphragm 250.
Methanol vapour flows up upcomer 252 as indicated by arrow
257, through the space between upcomer 252 and cap 253 as
indicated by arrows 258, and through skirt 254 as indicated
by arrows 259, and carries with it water vapour resulting
from water of esterification formed in a lower tray or
trays.

The plant of Figure 6 is generally similar to that
of Figure 1 and like reference numerals have been used in
both Figures to indicate like parts. The feed acid in line
4 is typically an unsaturated fatty acid, such as oleic
acid.

In the plant of Figure 6 line 2 is omitted so that
there is no recycle of methanol for admixture with the feed
methanol in line 1. Hence all of the methanol in line 45 is
supplied to wash tray 28.

As the number of theoretical stages in column 14
does not necessarily correspond to the number of trays 15
fitted in column 14, and the number of such theoretical
stages may vary, for a particular column, for different feed
acids supplied in line 4, the acid content of the methyl
ester product in line 23 may vary if the nature of the feed
acid in line 4 is changed.

As already mentioned a by-product of ester
formation in the column is often a dialkyl ether. The yield
of such dialkyl ether by-product is found to be dependent
upon the temperature of operation of the reactor 14. Hence

- 24 -

by minimising the temperature of operation of column reactor
14 the yield of by-product ether can be minimised. However,
a corollary of this is that a lower conversion of acid to
ester is obtained at lower operating temperatures. In this
case it is possible to optimise the conversion to ester by
admixing the ester-containing product, which contains
perhaps about 97 mole % to about 99 mole % of ester with the
balance being acidic materials, with further alkanol (e.g.
methanol) and passing the resulting mixture containing, for
example, a 2:1 to 4:1, e.g. 3:1, alkanol:ester molar mixture
through a polishing reactor having a fixed bed of a solid
esterification catalyst, such as Amberlyst 13, which can be
operated at a lower temperature than the column reactor. In
this way extremely high overall conversion to ester can be
achieved. Such a modified form of plant is illustrated in
Figure 6.

In the plant of Figure 6 there are six
esterification trays 15 and the methyl ester product in line
23 still contains a minor amount of oleic acid. Typically
the methyl oleate:oleic acid molar ratio is in the region of
97:3. This mixture is admixed with further methanol
supplied from line 301 to form a mixture having a molar
ratio of methanol:methyl oleate:oleic acid of 3:0.97:0.03.
This mixture is supplied in line 302 at a temperature of
60°C and at a liquid hourly space velocity of 1 hr^{-1} to a
further esterification reactor 303 containing a fixed bed
304 of an acidic ion exchange resin, such as Amberlyst 13.
The resulting mixture flows on in line 305 to a further
distillation column 306. Methanol vapour passes overhead
via line 307 to column 29 via line 26. Liquid methanol to
form a reflux stream and the stream in line 301 is pumped
from condensate drum 32 by pump 35 through line 308. The
reflux stream flows on in line 309 to column 306. The
bottom product from column 306 in line 310 comprises
essentially pure methyl oleate (of purity at least 99.5 mole

- 25 -

%). Part is recycled to column 306 by way of line 311 via
column reboiler 312 and line 313, whilst the remainder is
passed to storage or onward for further treatment in line
314.

The plants of Figures 1 and 2 and the trays 15
illustrated in Figures 3 and 4 have been described in the
context of acid containing liquid phase downflow and
upcoming vaporous alcohol flow. If the acid used is more
volatile than the alcohol component, then the directions in
which the acid and alcohol components flow can be reversed,
so that the alcohol is in liquid phase and flows down from
one tray 15 to the next downward tray 15 through reactor 14
whilst acid vapour passes upwardly in countercurrent
thereto.

The invention is further illustrated in the
following Examples.

Example 1

A laboratory scale column reactor with an internal
diameter of 76.2 mm made of glass QVF components and having
ten trays one above another was used. Each tray had the
form illustrated in Figure 5. The column reactor was lagged
and wound with external electrical heating tapes. Each tray
had its own temperature control system. The top tray
contained no resin and acted as a liquid scrubbing tray to
limit losses of the acid feed or of the ester product. The
second tray from the top also contained no resin and was
supplied with the acid feed. The remaining eight trays each
held a charge of Amberlyst 16 ion exchange resin which had
been sieved to remove beads with a particle size less than
355 μm and then washed extensively with methanol and then
dried at 105°C to constant weight. The mesh size of the
stainless steel mesh of skirt 254 and of cap 256 was 300 μm.
Dry methanol was vaporised by passage through a coil
immersed in an oil bath at 150°C and the resulting vapour
was fed to the bottom of the column reactor below the

lowermost tray. Each tray held about 240 ml of liquid. The resin charge on each tray corresponded to 14% by weight calculated as dry resin based on the liquid charge on each tray. The overhead vapour from the column reactor, which consisted of unreacted methanol, water which is produced in the course of esterification, and a minor amount of by-product dimethyl ether, was condensed. A constant head overflow device was used to control the rate of removal of product esters from the column reactor.

At start up the column reactor was charged with resin and with methyl laurate. When the methanol flow and the temperatures of the various trays had stabilised a feed of 50 mole % methyl laurate, 40 mole % lauric acid, and 10 mole % myristic acid was supplied to the column. This feed mixture was similar to the mixture in line 20 of Figure 1 when that plant is supplied in line 4 with a mixture of lauric acid and myristic acid. The level of C_{14} ester in the bottoms product from the column reactor was monitored until an equilibrium level was attained. The liquid on each tray was analysed. The results are summarised in Table I below; the trays are numbered from 1 to 10, tray No. 1 being the top tray and tray No. 10 being the bottom tray.

- 27 -

Table I

MeOH:Acid mole ratio	5:1	3.6:1	3:1
Residence time (hours)	2.6	2.2	2.0
Tray No.	Mole %	Conversion	
5	98.32	96.53	96.16
6	99.39	98.76	97.05
7	99.62	99.15	97.25
8	99.87	99.45	98.74
9	99.93	99.75	99.48
10	ND	99.81	99.76
DME make	3.0	2.7	1.5

In Table I and in the following Tables "N.D" means "not determined", whilst "DME" means "dimethyl ether", the "DME make" being expressed as a percentage by weight of the acid feed.

Example 2

The same column reactor as was used in Example 1 was fed with a mixture of natural straight chain fatty acids of the following composition:

Component	% by weight
C_8 acid	5.10
C_{10} acid	4.62
C_{12} acid	40.64
C_{14} acid	14.12
C_{16} acid	9.57
C_{18} acids	25.01
Unknowns	0.77
H_2O	0.17

The results are summarised in Table II.

- 28 -

Table II

MeOH: Acid mole ratio	2.7:1	3.8:1	4.2:1	4.1:1	4.7:1	6.7:1
Residence Time (hours)	1.9	3.3	3.6	3.5	4.6	4.7
Tray No	Mole % Conversion					
5	61.22	66.54	68.89	68.01	69.02	79.82
6	ND	ND	ND	ND	ND	ND
7	86.20	89.74	91.78	90.16	91.78	92.38
8	92.50	94.62	96.14	95.29	96.22	98.07
9	95.28	97.46	98.15	97.68	98.11	99.20
10	97.53	98.77	99.12	98.90	99.30	99.64
DME Make	2.0	2.8	2.5	2.7	2.7	2.8
Average Temperature (°C)	112	107	104	111	112	113

Example 3

The procedure of Example 2 was repeated using a 51.6:48.4 acid:ester mole ratio feed mixture. Such a mixture corresponded to a typical feed mixture in line 20 of Figure 1. The acids used were a mixture of natural straight chain fatty acids comprising 65% by weight C_{12} acid, 25% by weight C_{14} acid, and 10% by weight C_{16} acid. The results are shown in Table III below. In this Example the amounts of resin on a dry basis used on each tray corresponded to 10% by weight based upon the liquid retained for each of

SUBSTITUTE SHEET

trays Nos. 3 to 7 and to 5% by weight on the same basis for
trays Nos. 8 to 10.

<p align="center">Table III</p>

MeOH:acid mole ratio   3:1   2:1.
Residence time (hours)   2.5   2.5

Tray No	Mole % Conversion	
3	70.08	67.10
4	83.10	79.21
5	91.59	88.48
6	96.4	94.46
7	98.55	97.39
8	99.13	98.24
9	99.49	98.87
10	99.68	99.27
DME Make	2.1	1.3
Average temperature (°C)	110	107

Example 4

        The column reactor of Example 1 was used to
investigate the esterification of monoethyl maleate (MEM)
with ethanol (EtOH) to form diethyl maleate (DEM). The
resin loadings of the trays were the same as in Example 3.
The acid feed to tray No. 2 had the following composition in
mole %: H_2O 25.9; EtOH 20.3; DEM 10.4; diethyl fumarate
(DEF) < 0.1; MEM 39.4; monoethyl fumarate (MEF) 0.1; maleic
acid (MAC) 3.9; fumaric acid (FAC) < 0.1; diethyl
ethoxysuccinate (EDES) < 0.1. A wet ethanol replaced the
dry methanol used in Examples 1 to 3; this had the following
composition in mole %: EtOH 84.2; H_2O 15.8. The residence

- 30 -

time in the column reactor was approximately 2.7 hours. The
feed rates were 680 g/hr acid feed and 390 g/hr EtOH. The
results are shown in Table IV.

Table IV

Liquid Composition, mole %

Tray No.	H₂O	EtOH	DEM	DEF	MEM	MEF	MAC	FAC	EDES	Temp. (°C)	Mole % conv.
3	17.1	13.7	27.9	0.4	35.1	0.9	4.6	0.1	<0.1	119	41.0
4	16.7	18.9	33.4	0.5	26.8	0.7	2.9	0.1	<0.1	113	52.7
5	15.4	28.0	34.0	0.6	20.0	0.5	1.5	<0.1	<0.1	110	61.0
6	11.9	28.2	40.8	0.7	16.9	0.4	1.1	<0.1	<0.1	106	69.1
7	9.2	25.0	49.0	0.8	14.8	0.4	0.8	<0.1	<0.1	107	75.7
8	7.8	26.4	51.1	0.8	12.9	0.4	0.6	<0.1	<0.1	108	79.0
9	6.6	22.6	56.5	0.9	12.4	0.3	0.5	<0.1	<0.1	110	81.3
10	6.0	30.5	52.4	0.9	9.5	0.3	0.3	<0.1	<0.1	103	84.0

SUBSTITUTE SHEET

- 32 -

        In this Example diethyl ether was a by-product; the
amount of diethyl ether formed corresponded to approximately
16 g per kg of monoethyl maleate.

Example 5

        The procedure of Example 4 was repeated using the
same feed mixture but with a residence time in the reactor
of approximately 2.1 hours. The acid feed rate was 840 g/hr
and the ethanol feed rate was 475 g/hr. The results are
summarised in Table V.

Table V

Liquid Composition, mol %

Tray No.	H$_2$O	EtOH	DEM	DEF	MEM	MEF	MAC	FAC	EDES	Temp.(°C)	Mole % conv.
3	21.7	15.5	21.2	0.2	36.3	0.6	4.5	<0.1	<0.1	115	34.1
4	18.2	16.4	29.7	0.3	31.3	0.6	3.5	<0.1	<0.1	116	45.9
5	15.1	19.7	36.1	0.4	25.7	0.5	2.4	<0.1	<0.1	114	56.1
6	11.4	22.8	42.6	0.5	20.6	0.5	1.5	<0.1	<0.1	109	65.6
7	10.1	25.2	46.5	0.6	16.2	0.4	0.9	<0.1	<0.1	108	73.4
8	7.7	25.1	50.1	0.6	15.4	0.3	0.8	<0.1	<0.1	108	75.5
9	6.7	23.1	54.8	0.7	13.9	0.3	0.6	<0.1	<0.1	110	78.9
10	5.6	26.1	54.8	0.7	11.8	0.3	0.6	<0.1	<0.1	107	81.7

- 34 -

In this Example diethyl ether was a by-product; the amount of diethyl ether formed corresponded to approximately 11 g per kg of monoethyl maleate.

Examples 4 and 5 demonstrate the advantage of using the column reactor which enables mole % conversions of 84.0 and 81.7 to be achieved respectively using an alcohol:acid molar ratio of approximately 2:1. Using a fixed bed reactor it could be shown that the maximum mole % conversion would be approximately 72%, but it would then be necessary to use an alcohol:acid molar ratio of about 5:1. Similarly, when using a continuously stirred tank reactor conversions of 80% or higher could only be achieved if a similarly much higher alcohol:acid molar ratio was used, e.g. about 5:1 in place of approximately 2:1.

Example 6

Using the column reactor of Example 1 monomethyl maleate (MMM) was reacted with dry methanol (MeOH) under the conditions indicated in Table VI, which also lists the results obtained. The mole % conversion figures were obtained by titration.

Table VI

MeOH:MMM molar ratio	2.6:1	2.6:1
Residence time (hours)	3	2
Temperature (^{o}C)	108	111
Tray No.	Mole % conversion	
3	55.2	48.3
4	77.2	70.9
5	88.8	84.1
6	94.6	92.0
7	97.7	96.3
8	98.7	97.7
9	99.2	98.7
10	99.5	99.2

SUBSTITUTE SHEET

- 35 -

Example 7

The general procedure of Example 6 was followed to yield a product containing, besides a trace of water, substantially pure dimethyl maleate (DMM) but still containing a minor amount of monomethyl maleate (MMM). This product was admixed with dry methanol and passed in cocurrent through a polishing reactor containing Amberlyst 16 similar to reactor 304 of Figure 6. The results obtained are summarised in Table VII.

Table VII

LHSV (hr^{-1})	Temperature ($^{\circ}$C)	Mole% Conversion		Mole% H$_2$O in feed to reactor	MeOH:ester* molar ratio
		In	Out		
1.0	70	99.76	99.2	0.5	3.6:1
1.0	70	97.61	99.5	0.2	3.4:1
0.75	70	97.7	99.3	0.5	3.6:1
1.0	65	97.7	99.5	0.2	3.2:1

* The term "ester" here applies to the DMM/MMM mixture.

Example 8

Using the column reactor of Example 1 the following esterification reactions between the specified acid and the corresponding alcohol component are carried out with similarly good results with the more volatile reactant in each case being supplied to the bottom of the reactor in vapour form and the less volatile component being supplied in liquid form to the second tray of the reactor:

(a)   succinic acid and n-propanol to di-n-propyl succinate;

(b)   mono-n-butyl maleate and n-butanol to di-n-butyl maleate;

(c)   terephthalic acid and methanol to dimethyl terephthalate;

(d)   butyric acid and phenol to phenyl butyrate;

SUBSTITUTE SHEET

- 36 -

(e)   glutaric acid and ethanol to diethyl glutarate;

(f)   oxalic acid and ethanol to diethyl oxalate;

(g)   benzoic acid and ethanol to ethyl benzoate;

(h)   1-naphthoic acid and methanol to methyl 1-naphthoate;

(i)   acetic acid and ethylene glycol to ethylene glycol diacetate;

(j)   stearic acid and methanol to methyl stearate;

(k)   palmitic acid and ethanol to ethyl palmitate;

(l)   arachidic acid and methanol to methyl arachidate;

(m)   butyric acid and n-nonanol to n-nonyl butyrate;

(n)   citric acid and ethanol to ethyl citrate; and

(o)   formic acid and propylene glycol to propylene glycol diformate;

(p)   oleic acid and iso-propanol to iso-propyl oleate;

(q)   ricinoleic acid and methanol to methyl ricinoleate; and

(r)   isostearic acid and methyl to methyl isostearate.

CLAIMS

1.   A continuous process for the production of
carboxylic acid esters by reaction of a carboxylic acid
component selected from mono-, di- and polycarboxylic acids,
anhydrides thereof, and mixtures thereof, and of an alcohol
component selected from mono-, di- and polyhydric alcohols,
phenols and mixtures thereof, in which the carboxylic acid
component and alcohol component are passed in countercurrent
through an esterification zone maintained under
esterification conditions and containing a solid
esterification catalyst selected from particulate ion
exchange resins having sulphonic acid groups, carboxylic
acid groups or both, characterised in that the
esterification zone comprises a column reactor provided with
a plurality of esterification trays mounted one above
another, each adapted to hold a predetermined liquid volume
and a charge of solid esterification catalyst thereon,
liquid downcomer means associated with each esterification
tray adapted to allow liquid phase to pass down the column
reactor from that esterification tray but to retain solid
esterification catalyst thereon, and vapour upcomer means
associated with each esterification tray adapted to allow
vapour to enter that esterification tray from below and to
agitate the mixture of liquid and solid esterification
catalyst on that tray, that the less volatile component of
the carboxylic acid component and of the alcohol component
is supplied in liquid phase to the uppermost one of said
plurality of esterification trays whilst the more volatile
component of the carboxylic component and of the alcohol
component is supplied in vapour form beneath the lowermost
one of said plurality of esterification trays, that vapour
comprising said more volatile component and water of
esterification is recovered from an upper part of the column
reactor, and that said carboxylic acid ester is recovered
from a lower part of the column reactor.

- 38 -

2.   A process according to claim 1, <u>characterised in
that</u> the more volatile component is the alcohol component
and <u>that</u> the less volatile component is the carboxylic acid
component.

3.   A process according to claim 1 or claim 2,
<u>characterised in that</u> the alcohol component is an alkanol
containing from 1 to about 10 carbon atoms.

4.   A process according to claim 3, <u>characterised in
that</u> the alkanol is methanol.

5.   A process according to claim 3 or claim 4,
<u>characterised in that</u> the water content of the alkanol
vapour supplied to the column reactor is less than about 5
mole %.

6.   A process according to any one of claims 1 to 5,
<u>characterised in that</u> the carboxylic acid component is an
aliphatic monocarboxylic acid or a mixture thereof.

7.   A process according to claim 6, <u>characterised in
that</u> the carboxylic acid component is a mixture of fatty
acids.

8.   A process according to any one of claims 1 to 5,
<u>characterised in that</u> the carboxylic acid component is
selected from maleic acid, fumaric acid, maleic anhydride, a
monoalkyl maleate, a monoalkyl fumarate, and mixtures of two
or more thereof.

9.   A process according to any one of claims 1 to 8,
<u>characterised in that</u> the column reactor is operated at a
temperature of from about 80°C to about 140°C and at a

- 39 -

pressure of from about 1 bar to about 25 bar.

10.   A process according to any one of claims 1 to 9,
characterised in that the carboxylic acid ester recovered
from a lower part of the column reactor is admixed with
further alcohol component and is passed through a fixed bed
of a solid esterification catalyst.

11.   Apparatus for use in the production of a carboxylic
acid ester by reaction of a carboxylic acid component
selected from mono-, di- and polycarboxylic acids,
anhydrides thereof, and mixtures thereof, and of an alcohol
component selected from mono-, di- and polyhydric alcohols,
phenols and mixtures thereof, comprising a column reactor
provided with a plurality of esterification trays mounted
one above another, each adapted to hold a predetermined
liquid volume and a charge of a solid esterification
catalyst thereon, liquid downcomer means associated with
each esterification tray adapted to allow liquid phase to
pass down the column reactor from that esterification tray
but to retain solid esterification catalyst thereon, vapour
upcomer means associated with each esterification tray
adapted to allow vapour to enter that esterification tray
from below and to agitate the mixture of liquid and solid
esterification catalyst on that esterification tray, means
for supplying the less volatile component of the carboxylic
acid component and of the alcohol component in liquid phase
to an upper part of the column reactor above the uppermost
esterification tray, means for supplying the more volatile
component of the carboxylic acid component and of the
alcohol component in vapour form to a lower part of the
column reactor below the lowermost esterification tray,
means for recovering carboxylic acid ester from a lower part
of the column reactor below the lowermost esterification
tray, and means for recovering from an upper part of the

- 40 -

column reactor above the uppermost esterification tray a
vaporous stream comprising said more volatile component and
water of esterification.

12.   Apparatus according to claim 11, in which said
vapour upcomer means comprises a sparger positioned so that,
in operation, it will lie below the surface of the mixture
of liquid and solid esterification catalyst and so that
vapour bubbles emerging therefrom will agitate said mixture
of liquid and catalyst.

13.   Apparatus according to claim 12, in which the
sparger is a ring sparger.

14.   Apparatus according to claim 12 or claim 13, in
which at least one baffle means is mounted in the vicinity
of the sparger to enhance the mixing action thereof.

15.   Apparatus according to claim 14, in which inner
and outer annular baffle means are positioned in the
vicinity of the sparger and define an upflow zone in the
region of upflowing vapour bubbles and adjacent downflow
zones within and outside the upflow zone.

16.   Apparatus according to any one of claims 12 to 15,
in which the floor of at least one of the esterification
trays slopes towards a zone under the sparger.

17.   Apparatus according to any one of claims 12 to 16,
in which the vapour upcomer means of at least one
esterification tray is provided with a suckback preventer
means.

18.   Apparatus according to any one of claims 12 to 17,
in which a screen means is provided on at least one

- 41 -

esterification tray to hinder loss of solid esterification catalyst from that esterification tray via its associated downcomer means.

19.   Apparatus according to any one of claims 11 to 18, which includes a further reactor containing a fixed bed of a solid esterification catalyst connected downstream from the column reactor and means for admixing additional alcohol component with the carboxylic acid ester component recovered from a lower part of the column reactor prior to entry to the further reactor.

FIG.1

FIG.2

FIG.3

FIG.4

FIG.5

FIG.6